

PLEION

MAINTENANCE

2018

Pleion products are designed with a minimum of maintenance in mind. All surface materials are easily cleaned, using the following procedures. PLEION Is the easiest & Fastest to Install.

PANELS

Baked Epoxy Powdercoat

All exposed surfaces are coated with a baked epoxy powdercoat finish. Dust regularly. Clean soiled areas with a mild, non-abrasive cleaner.

Fabric

Standard Pleion fabrics are 100% polyester. Wool fabrics are available. Brush off dust and dirt with a clean brush having flexible bristles. Remove soiled areas by lightly spraying with a foam fabric or carpet cleaner. NOTE: Do not soak fabric area being cleaned: this could pull fiberglass particles through the fabric.

Permanently damaged fabric may be replaced by purchasing a new piece. Replacement can be accomplished without removing the panel from the installation. Simply cut a new piece of fabric to the size of the frame and tuck it into place using our special tucking tool.

Plexy glass

Standard glass cleaning products may be used for cleaning plexiglass panels.

Metal

The raceway covers may be cleaned with the same method as the panels. Take care not to use abrasive cleaners.

Alignment

Corner pads and run-end pads have been equipped with carpet grippers to keep them in place. Should any movement become necessary, lift panel and replace in new position on carpet.

FURNITURE

Baked Epoxy Powdercoat

All components can be cleaned by using the same method as described for panels.

Laminate

Pleion work surfaces and countertops can be cleaned with a non-abrasive, all purpose spray cleaner. 301 E, Stevens Ave . Santa Ana Ca 92707 PLEION
Information : 1-714-480-9000

www.pleion.com